

Shandong Ruiwang Industrial Technology Co., Ltd.

1818 Chongwen Street, Fangzi district, Weifang, Shandong Prov

Email: rw04@rinwang.com

Tel: 86-571 88053366 Mobile: +86 19706828442

Specification Sheet

Model	RW-600M	Reference image for model
Name	Industrial Desiccant Dehumidifier	
Dehumidifying capacity	3.0kg/hour	
Process air flow (m3/h)	580	
Reactivation air flow(m3/h)	200	
Reactivation heating(°C)	110± 10	
Installed power(KW)	4.5	
Unit Dimension (mm)	585*420*866	
Product Weight (kg)	70	
Power Source	220V/50Hz	
Work Temperature	-5°C to +50°C	
Package	wooden case	

Features:

- 1.High quality desiccant rotor,washable,5 years lifetime, warranty 1 years
- 2.Equipped with an electric regeneration heating;
- 3.PLC controller, smart control system ensures inside temperature constant,do reliable and stable performance.
- 4.Access door design for easier maintenance and troubleshooting;
- 5.Customized filters,G4 efficiency;
- 6.Auto stop protection function for Rotor;
- 7.Delay time protection circuit & fault locator system;

Specification Sheet

Model	RW-1000M	Reference image for model
Name	Industrial Desiccant Dehumidifier	
Dehumidifying capacity	7.5kg/hour	
Process air flow (m3/h)	1200	
Reactivation air flow(m3/h)	450	
Reactivation heating(°C)	110± 10	
Installed power(KW)	11.00	
Unit Dimension (mm)	875*640*1232	
Product Weight (kg)	160	
Power Source	380V/50Hz	
Work Temperature	-5°C to +50°C	
Package	wooden case	

Features:

- 1.High quality desiccant rotor,washable,5 years lifetime, warranty 1 years
- 2.Equipped with an electric regeneration heating;
- 3.PLC controller, smart control system ensures inside temperature constant,do reliable and stable performance.
- 4.Access door design for easier maintenance and troubleshooting;
- 5.Customized filters,G4 efficiency;
- 6.Auto stop protection function for Rotor;
- 7.Delay time protection circuit & fault locator system;

Specificaion sheet

Model	RW-2500M	
Name	Industrial Desiccant Dehumidifier	
Dehumidifying capacity	18kg/hour	
Process air flow (m3/h)	2500	
Reactivation air flow(m3/h)	850	
Reactivation heating(°C)	110± 10	
Installed power(KW)	28.0	
Unit Dimension (mm)	1760x1040x1100mm	
Product Weight (kg)		
Power Source	380V/50Hz	
Work Temperature	-10~50°C	
Package	wooden case	

Features:

- 1.High quality desiccant rotor,washable,5 years lifetime, warranty 1 years
- 2.Equipped with an electric regeneration heating;
- 3.PLC controller, smart control system ensures inside temperature constant,do reliable and stable performance.
- 4.Access door design for easier maintenance and troubleshooting;
- 5.Customized filters,G4 efficiency;
- 6.Auto stop protection function for Rotor;
- 7.Delay time protection circuit & fault locator system;

Specificaion sheet

Model	RW-4500M	
Name	Industrial Desiccant Dehumidifier	
Dehumidifying capacity	57kg/hour	
Process air flow (m3/h)	4500	
Reactivation air flow(m3/h)	1350	
Reactivation heating(°C)	110± 10	
Installed power(KW)	50	
Unit Dimension (mm)	1510*760*1060	
Product Weight (kg)		
Power Source	380V/50Hz	
Work Temperature	-10~50°C	
Package	wooden case	

Features:

- 1.High quality desiccant rotor,washable,5 years lifetime, warranty 1 years
- 2.Equipped with an electric regeneration heating;
- 3.PLC controller, smart control system ensures inside temperature constant,do reliable and stable performance.
- 4.Access door design for easier maintenance and troubleshooting;
- 5.Customized filters,G4 efficiency;
- 6.Auto stop protection function for Rotor;
- Delay time protection circuit & fault locator system;