

Model	RW-300M	RW-600M	RW-750M	RW-1000M	RW-1500M	RW-3000M
Poweer	220V/50Hz	220V/50Hz	380V/50Hz	380V/50Hz	380V/50Hz	380V/50Hz
capacity	2. 5kg/h	3. 0kg/h	4. 5kg/h	7. 5kg/h	10kg/h	19kg/h
Test condition	T=20℃, RH=60%	T=20℃, RH=60%	T=20℃, RH=60%	T=20℃, RH=60%	T=20℃, RH=60%	T=20℃, RH=60%
Rated power	2. 0KW	4. 5KW	7KW	11KW	15KW	30KW
Current rating	9A	20A	14A	18A	26A	50A
Handling airflow	320m3/h	800m3/h	950m3/h	1100m3/h	1550m3/h	3000m3/h
Regeneration air volume	110m3/h	200m3/h	250m3/h	450m3/h	550m3/h	1100m3/h
Deal with wind residual pressure	80Pa	100Pa	120Pa	150Pa	200Pa	400Pa
Regenerative air residual pressure	50Pa	70Pa	80Pa	100Pa	150Pa	200Pa
Handle the wind caliber	Φ 125mm*2	Φ 125mm*2	Φ 200mm*2	Φ 200mm*2	Φ 250mm*2	522*286/Φ 400mm
Regenerative air caliber	Φ 80mm*2	Φ 100mm*2	Φ 125mm*2	Φ 150mm*2	Φ 160mm*2	Φ 200mm*2
Apply Temperature	-10到+50℃	-10到+50℃	-10到+50℃	-10到+50℃	-10到+50℃	-10到+50℃
Machine size	680*425*400mm	585*420*866mm	1090*600*671mm	875*640*1232mm	880*678*1238mm	1312*856*1300mm
Weight	45 kg	70 kg	110 kg	160 kg	180 kg	300 kg
Picture						